

NP-VG2HD

NP-VG2HD is VGA and Audio to HDMI Scaler Converter.

For video input, VGA video is supported. Input video signal is converted to HDMI signal at resolutions up to 1080p.

For audio input, analog audio and S/PDIF are supported and those signals are converted to HDMI signal.

■ Specification

Item			Description	
Input	Video	Universal Analog	Number / Signal	1 input / Analog RGB - Analog RGB: 0.7 V [p-p]
			Connector	female 15-pin HD
		Format	Analog SVGA / XGA / WXGA(1280x800) / SXGA / UXGA / WSXGA+ / 576p / 720p / 1080p EDID is always 1080p	
	Audio	Digital	Number / Signal	1 input / S/PDIF
		Analog	Number / Signal	1 input / Stereo LR unbalanced signal
Connector	1 RCA pin jack			
Output	Video	HDMI / DVI	Number / Signal	1 output / HDMI
			Connector	1 female HDMI Type A (19-pin)
		Format	VGA / SVGA / XGA / SXGA / WXGA (1280x800) / UXGA / WSXGA+ / 1920 x 1080* / WUXGA* / 480i / 480p / 576i / 576p / 720p / 1080i / 1080p * 1920 x 1080 / WUXGA are only output as Reduced Blanking	
	Audio	Digital	Number / Signal	1 output
			Connector	1 female HDMI Type A (19-pin),
	Scan Converter			Picture adjustment (brightness, contrast), Test pattern
	Others			H-Mirror, V-Mirror, H-Shift, V-Shift
Others	Power			DC 5V 4A
	Power consumption			About 5 Watts
	Dimensions			92 (W) × 28(H) × 83 (D) mm (Excluding connectors and the like)
	Weight			0.29 kg
	Temperature			Operating: 0 °C to +40 °C Storage: -20 °C to +60 °C

*CEC, ARC and HEC in HDMI are not supported.

■ Appearance

